

CABLING

SABS



FLAT TWIN AND EARTH CABLE



Description

Solid or stranded plain copper conductors, PVC insulated, laid up with bare copper earth wire, PVC sheathed overall.

Specification: SANS 1507-2

Voltage Rating	300/500V
Temperature Range	-10°C to 70°C
Sheath colours	Black and white
Core colours	2 core – Black and Red 3 core – Blue, Red and Yellow

Installation Information

Complies with SANS 10142/2001 "Code of Practice for the wiring of Premises" Section 6, Clause 6.3.6:

- Surface wiring
- Under-plaster wiring
- Roof access wiring
- Wiring in hollow walls

Application

For the wiring of Under-plaster wiring, Roof wiring, Under-floor wiring.

Properties

Specification	SANS 1507-2
Temperature Range	-10°C to 70°C
Voltage Rating	300 / 500V
Sheath Identification	White & Black
Core Identification	2 Core – Red & Black 3 Core – Red, Yellow, Blue
Packaging	100m shrink – wrapped coils

SURFACE WIRING

SABS



Description

Plain copper conductors, PVC insulated, laid up with a tinned earth wire in contact with a longitudinal Aluminium foil tape, PVC sheathed overall.

Specification: SANS 1507-2

Voltage Rating	300/500V
Temperature Range	-10°C to 70°C
Sheath colours	Black and white
Core colours	2 core – Black and Red 3 core – Blue, Red and Yellow 4 core – Black, Blue, Red and Yellow

Application

For the wiring of Under-plaster wiring, Roof wiring, Under-floor wiring, Surface wiring.

Stock and availability upon request. Additional sizes available on request. Data subject to change without prior notice. This data cancels all previous data. Every effort has been made to ensure the accuracy of this data, Kamarossi does not accept responsibility for any errors or omissions.